

DROP SIDE



The AW Dropside Trailers are designed for general use. These trailers are available with 460mm (18") or 915mm (36") high sides. They can be used with or without the sides, which are completely removable. The headboard remains fixed. With options of a bale extension and extension sides, this trailer can be used for a wide variety of tasks.

STANDARD FEATURES

- Fixed Headboard
- Rope Hooks
- Hydraulic Brakes & Ratchet Handbrake
- 3mm Thick Sides
- 2 Pack Primer & Top Coat
- Heavy Duty Multi-Leaf Sprung Axles (8T Model)
- 4mm Thick Floor
- Top Hinged Tailboard
- Hydraulic Tipping Rams
- Maintenance Free LED Lights
- Body Prop
- Shot Blasted

	3T Dropside	4T Dropside	5T Dropside	6.5T Dropside	8T Dropside
Length (Internal) (A)	2740mm/9'	3200mm/10'6"	3350mm/11'	3660mm/12'	4300mm/14'
Width (Internal)	1730mm/5'8"	2000mm/6'6"	2130mm/7'	2285mm/7'6"	2440mm/8'
Body Height (B)	460mm/18"	460mm/18" 915mm/36"	460mm/18" 915mm/36"	460mm/18" 915mm/36"	460mm/18" 915mm/36"
Capacity - 460mm (18")	2.2m ³ /78ft ³	2.95m ³ /102ft ³	3.28m ³ /115ft ³	3.72m ³ /135ft ³	4.83m ³ /168ft ³
Capacity - 920mm (36")	N/A	5.9m ³ /205ft ³	6.56m ³ /231ft ³	7.44m ³ /270ft ³	9.65m ³ /336ft ³
Chassis	125 x 65 PFC	125 x 65 PFC	150 x 75 PFC	180 x 75 PFC	250 x 150 RHS
Axle Size	60mm 6 Stud (Single)	60mm 6 Stud (Single)	70mm 6 Stud (Single)	80mm 6 Stud (Single)	80mm 6 Stud (Tandem)
Brake Size	250 x 60	250 x 60	300 x 60	300 x 60	300 x 60
Wheel Track	1500mm/59"	1700mm/67"	1800mm/67"	1900mm/75"	2000mm/79"
Tyre Size	10/75 x 15.3	10/75 x 15.3	11.5/80 x 15.3	12.5/80 x 15.3	12.5/80 x 15.3
O/a Length (C)	3950mm/13'	4400mm/14'5"	4640mm/15'3"	4950mm/16'3"	5750mm/18'10"
O/a Width	1850mm/6'1"	2070mm/6'10"	2130mm/7'	2285mm/7'6"	2440/8'
O/a Height (D)*	1300mm/4'3"	1300/4'3"	1390mm/4'7"	1405mm/4'7"	1570/5'2"
Max Tipped Height (E)*	2890mm/9'6"	3480mm/11'5"	3680mm/12'1"	3760mm/12'4"	4220mm/13'10"
Unladen Weight	1.1 Tonne Approx.	1.3 Tonne Approx.	1.6 Tonne Approx.	1.9 Tonne Approx.	2.8 Tonne Approx.

*Based on 460mm (18") high sided version (for 915mm/36" high side, add 460mm to overall & 300mm to tipped heights). For optional extras, see pages 36 & 37