ULTIMA



The AW Ultima range of trailers is a high-quality grain & root crop haulage trailers. They feature large capacity bodies with our sleeker, stronger body profile with wide side channels and extra floor supports. When fitted with silage sides or rollover sheet, this is the perfect all-round trailer to have on the farm.

STANDARD FEATURES

- Large Capacity Body with Smooth Interior & Exterior
- 90 x 90 Thick Walled RHS Box Top Runners
- Heavy Duty RHS Rear Cross Member
- Extra Wide Channels Forming Strong Ribs Around Sides & Floor
- Hydraulic Brakes & Ratchet Parking Brake
- High-Capacity Chrome Hydraulic Tipping Rams
- Heavy Duty Parabolic Suspension with 420 x 180 Braked Axles
- Rear Towing Points
- Commercial quality easy change number plate holder
- Completely Shotblasted
- Choice of Body Colour (within Standard Tractor Colour Range)
- 560/60R22.5 Flotation Tyres
- Body Prop
- 5mm Thick Floor & 4mm Thick Sides
- 200 x 100 Thick Walled RHS Box Corner Posts
- Heavy Duty Rope Hooks
- Removable Skid
- Hydraulic Load Sensing
- Commercial Maintenance Free LED Lights including Double Rear, Front & Side
- Front Inspection Steps
- Sprung Drawbar with Multi- adjustable height positions
- Bulkhead Couplings
- 2 Pack Primer & Top Coat
- Grey Painted Chassis
- Contractor Hydraulic Tailboard
- Front Window c/w Polycarbonate Screen
- Flashing Beacon

Ultima Xtra Upgrade

Available in all Ultima models, featuring sleeker Hardox 450 body (3.2mm sides & 4mm floor), extra Hi-Viz, beacon, extra high level lights & front mudflaps






AW TRAILERS
Ultima


Ultima
AW TRAILERS
Ultima


Ultima
AW TRAILERS
Ultima


AW TRAILERS
Ultima


CELEBRATING
30
YEARS
ANNIVERSARY
AW TRAILERS
Ultima


AW TRAILERS
Ultima Xtra
HARDOX

ULTIMA MONO SPECIFICATIONS

	Ultima 12T Mono	Ultima 14T Mono	Ultima 16T Mono	Ultima 18T Mono	Ultima 20T Mono	Ultima 24T Mono
Length (Internal) (A)	5505mm/18’	6100mm/20’	6700mm/22’	7300mm/24’	7300mm/24’	9000mm/29’6”
Width (Internal)	2275mm/7’6”	2275mm/7’6”	2275mm/7’6”	2275mm/7’6”	2275mm/7’6”	2275mm/7’6”
Body Height (B)	1345mm/4’5”	1345mm/4’5”	1345mm/4’5”	1345mm/4’5”	1525mm/5’	1525mm/5’
Cubic Capacity - Grain	16.8^3/597ft^3	18.7^3/663ft^3	20.5^3/729ft^3	22.5m^3/795ft^3	25.3^3/899ft^3	31m^3/1095ft^3
Chassis	250 x 150 RHS	250 x 150 RHS	250 x 150 RHS	250 x 150 RHS	250 x 150 RHS	300 x 200 RHS
Axle Size	127mm Round 10 Stud (Tandem)	127mm Round 10 Stud (Tandem)	127mm Round 10 Stud (Tandem)	127mm Round 10 Stud (Tandem)	127mm Round 10 Stud (Tandem)	127mm Round 10 Stud (Tri-Axle + Rear Steer)
Brake Size	420 x 180	420 x 180	420 x 180	420 x 180	420 x 180	420 x 180
Wheel Track	2000mm/79”	2000mm/79”	2000mm/79”	2000mm/79”	2000mm/79”	2000mm/79”
Tyre Size	560/60R22.5	560/60R22.5	560/60R22.5	560/60R22.5	560/60R22.5	560/60R22.5
Suspension	4 Leaf Parabolic 75mm	3 Leaf Parabolic 100mm	3 Leaf Parabolic 100mm	3 Leaf Parabolic 100mm	3 Leaf Parabolic 100mm	3 Leaf Parabolic 100mm
O/a Length (C)	7050mm/23’2”	7645mm/25’1”	8245mm/27’1”	8870mm/29’1”	8870mm/29’1”	10570mm/34’7”
O/a Width	2475mm/8’2”	2475mm/8’2”	2475mm/8’2”	2475mm/8’2”	2475mm/8’2”	2475mm/8’2”
O/a Height (D)	2810mm/9’2”	2775mm/9’1”	2775mm/9’1”	2775mm/9’1”	2955mm/9’8”	2955mm/9’8”
Max Tipped Height (E)	6305mm/20’8”	6730mm/22’1”	7330mm/24’	7670mm/25’2”	7790mm/25’7”	9100mm/29’8”
Unladen Weight	5.0 Tonne Approx.	5.3 Tonne Approx.	5.7 Tonne Approx.	6.1 Tonne Approx.	7.0 Tonne Approx.	8.0 Tonne Approx.

For Ultima Xtra (Hardox) upgrade & optional extras, see pages 36 & 37